

Interstrip Paint Remover

One-Pack Paint Remover

New from International® Paint is Interstrip Paint Remover, designed to remove single component yacht paints such as enamels, antifoulings, primers and varnishes.

Interstrip Paint Remover works by softening or blistering the paint allowing easy removal with a scraper. There is no need to cover up the hull after application. Unlike traditional solvent-based paint removers Interstrip Paint Remover continues to dissolve the underlying paint as long as 12+ hours after application.



FEATURES AND BENEFITS:

- Easy to use.
- Suitable for use on all substrates including GRP.
- Virtually odourless in comparison to other paint removers.

Interested? Please contact your local international representative or visit www.yachtpaint.com for further information.

PRODUCT DATA

Product Code and Colour: YMA175 - White

Shelf life: 2 yrs

Application method: Brush, Roller or Airless Spray

Cleaner: Water or YTA085 Thinners No.3

Pack Size: 5LT



SURFACE PREPARATION AND SYSTEM



Wash off loose coating with fresh water, preferably at high pressure. Mask off areas to be stripped.



Apply liberally with an old broad brush (75-150mm) using a stippling action to get a good thickness or alternatively apply by spray or roller. Leave on the surface for at least 45 minutes to ensure easy removal. It is recommended that the product is removed when soft (max 12 hrs) in order to make the job quicker and easier. Use a blunt wooden scraper to remove soft paint. Heavy build up may require more than one application.



Use of cling-film or a similar product if the product is to be left for more than 4 hours to prevent it from drying out.


See Product Datasheet for further details.

Related Products:

- YTA085International Antifouling Thinners No. 3

Important Notes:

The information in this sheet is not intended to be exhaustive; any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk. Any warranty, if given, or specific conditions of sale are contained in International Paint's Conditions of Sale, a copy of which can be obtained on request. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so and to the extent permitted by law, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

 and **International**, are registered trademarks of, or licensed to, Akzo Nobel.
© Akzo Nobel, 2004
International Coatings Ltd., 24-30 Canute Road, Southampton, Hampshire, SO14 3PB.
Tel: 023 8022 6722 Fax: 023 8033 5975

