

Perfection Varnish

PRODUCT DESCRIPTION

The ultimate in varnish performance combining excellent chemical and abrasion resistance with superb gloss

Perfection Varnish is the premium high performance clear varnish, for beautiful wood with a tough finish. The ultimate product for durability, gloss retention and UV-resistance.



Pack size: 750ml / 2.5Lt
Product Code: YVA853-Clear

KEY FEATURES AND BENEFITS

- High performance two-part clear polyurethane varnish, for use above the waterline.
- UV filters combine with chemical cure to give the longest possible life, up to four times longer service than ordinary varnishes.
- Chemical cure gives resistance to abrasion, fuels, oils, mild acids and alkalis.
- High gloss finish with excellent clarity, which brings out the best in wood.
- Brushes easily with excellent levelling properties, and hardens into an extremely tough, weather-resistant, clear coating.
- Excellent coating for clear epoxys, such as Epiglass.



PERFECTION VARNISH PRODUCT DATA

PRODUCT CODE & COLOUR	YVA853-Clear
FINISH	Full gloss
THINNER	YTA006 Thinners No.9
NUMBER OF COATS	4 coats minimum
APPLICATION METHOD	Brush / Roller
PACK SIZES	750 ml / 2.5 Lt
CONVERTER/CURING AGENT	YVA850 Perfection Varnish Clear
TYPICAL SHELF LIFE	2 yrs

Refer to Perfection Varnish product data sheet for more information, including drying times.
Always read the label.

SURFACE PREPARATIONS AND SYSTEMS

Previously varnished wood in good condition – Clean with thinners. Sand with 280-320 grade paper.

Previously varnished wood in poor condition – Remove all previous coatings, follow scheme for bare wood.

Bare Wood – Sand smooth with 80-120 grade paper. Clean surface by brushing, dusting or wiping. If wiping with solvent then allow to dry completely before applying first coat of varnish. Priming bare wood: Apply Intertox or UCP. If UCP has been omitted, thin the first coat by 10-15% with Thinners No.9.

Clear Epoxy – Allow epoxy to cure for minimum of one week. Scrub with soap and

For full scheme specifications please refer to your local International Representative.

RELATED PRODUCTS

PRODUCT CODE	DESCRIPTION
YMA601	Fibreglass Surface Prep
YMA006	Thinners No.9

SYSTEMS AND COMPATIBILITY

Will crack on carvel and clinker / lapstroke hulls.

For use above the waterline only.

International Coatings Ltd., 24-30 Canute Road, Southampton.
Tel: 023 8022 6722 Fax: 023 8033 5975



* and International® are registered trademarks of International Coatings Ltd.
Akzo Nobel Logo is a registered trademark of Akzo Nobel NV.
Teflon is a registered trademark of DuPont.

Disclaimer

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

August 2006

