

# Schooner

## PRODUCT DESCRIPTION

**Premium high gloss varnish with UV protection.**

Schooner is a traditional tung oil based gloss yacht varnish for classic yachts, suitable for all internal and external wood. Schooner's high performance formulation contains UV absorbers for a long lasting, durable finish.



Pack size: 375ml / 750ml / 2.5Lt  
Product Code: YVA213-Clear

## KEY FEATURES AND BENEFITS

- Contains UV filters for remarkable gloss retention and long-lasting protection for wood.
- Excellent water resistance.
- Easy brush characteristics and silky application make Schooner extremely easy to apply.
- Excellent flow out and self-levelling properties, ensure a smooth finish with a deep luxurious gloss.
- Heavy-bodied for quick build up.
- Based on tung oil, Schooner dries to a lustrous, deep gloss finish, enhancing the natural beauty of wood.
- Warm golden coloured finish, enhances both interior and exterior wood work.



## SCHOONER PRODUCT DATA

<b>PRODUCT CODE &amp; COLOUR</b>	YVA086-Yellow Amber
<b>FINISH</b>	High Gloss
<b>THINNER</b>	Brush – Thinner No.333 / Spray Thinner No.3
<b>NUMBER OF COATS</b>	2 - 4 coats
<b>APPLICATION METHOD</b>	Brush / Roller / Conventional Spray / Airless
<b>PACK SIZES</b>	375 ml, 750 ml, 2.5 Lt
<b>TYPICAL SHELF LIFE</b>	2 yrs

Refer to Schooner product data sheet for more information, including drying times.  
Always read the label.

## SURFACE PREPARATIONS AND SYSTEMS

**Previously Varnished Wood in good condition** – Clean with Super cleaner. Sand smooth with 280-320 grade paper. Remove sanding dust with a dust wipe. Apply 2-4 full coats, until a satisfactory finish is achieved. Sand between coats using 320-400 grade paper. Remove dust with dust wipe.

**Poor surface condition:** Remove all previous coatings. Follow the system for bare wood.

**Bare Wood:** Sand smooth with 80-180 grade paper and then 280 grade paper. Clean surface by brushing, dusting or wiping. If wiping with solvent then allow to dry completely before applying first coat of varnish. Apply the first coat thinned 10% with Thinner No.333. Apply a further 4-6 coats until a satisfactory finish is achieved. Sand between coats using 320-400 grade paper. Remove with a dust wipe. Do not apply too thickly.

For full scheme specifications please refer to your local International Representative.

Do not apply Schooner straight from the can, this will cause it to age prematurely and may introduce contamination to the can.


## RELATED PRODUCTS

PRODUCT CODE	DESCRIPTION
Thinner No.333	For Brush Application
Thinner No.3	For Spray Application

## SYSTEMS AND COMPATIBILITY

Suitable for use on all types of wood, except direct application onto oily timbers such as Teak and Iroko.

International Coatings Ltd., 24-30 Canute Road, Southampton.  
Tel: 023 8022 6722 Fax: 023 8033 5975

 and International © are registered trademarks of International Coatings Ltd.  
Akzo Nobel Logo is a registered trademark of Akzo Nobel NV.  
Teflon is a registered trademark of DuPont.

### Disclaimer

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Revised April 2002

